

3 Mpixel IP-camera sensitive to 0.2 lux @ F 1.4
Frame Rate 22 fps @ Resolution 1,920 x 1,080

Made in the USA


The AV3100 Series offers cinema compatible frame rates to allow real time high definition digital video surveillance with 10 times the resolution of the best analog surveillance cameras.

- **SUPERB HIGH RESOLUTION & FULL MOTION:** AV3100 Series network camera delivers full motion progressive scan 1920 x 1080 video at 22 fps featuring massively-parallel MegaVideo® image processing architecture capable of sustaining over 6 billion operations per second.
- **SUPERB COST EFFICIENCY:** High resolution and crystal clear imagery allows the AV3100 Series to substitute up to ten analog cameras; thereby reducing the total cost of installation. No need to supply a separate power source since the power can be drawn from a low cost Power-over-Ethernet switch.
- **SUPERB FORENSIC ZOOMING:** AV3100 Series surveillance system has the ability to zoom in after any event from high resolutions digital archives. You can also simultaneously view zoomed and full field of view images.
- **24-HOUR SURVEILLANCE WITH DAY/NIGHT FEATURE:** The MegaVideo® single sensor Day/Night feature is especially useful where you need to capture images under highly variable lighting conditions, such as brilliant mid-day sun, and dim night. In daytime illumination, the camera operates in normal color mode providing vivid images, then automatically changes to black-and-white mode using IR cut filter removal technology when the light fades at dusk. The transition from day to night is fully programmable, or can be forced to either day or night mode.
- **ONBOARD MOTION DETECTION:** Onboard real-time motion detection with size and sensitivity controls for up to 64 separate motion detection zones.



Model Numbers

- AV3100M
3 Megapixel camera
- AV3100DN
3 Megapixel Day/Night camera with automatic IR cut Filter
- AV3100AI
3 Megapixel Camera w/Auto Iris



Power over Ethernet

Power for the camera is drawn from the network, reducing cabling requirements and installation time.



Local Area Network

Real-time viewing, archive storage and playback.



Internet

Real-time viewing/playback with selectable resolution.

Imaging

- 3 Megapixel CMOS Image Sensor
- 2048(H) x 1536(V) pixel array
- 1/2" Optical format
- 3.2 µm pixel pitch
- Bayer mosaic RGB filter
- Sensitivity 0.2 lux @ F1.4
- Dynamic Range 60 dB
- Maximum SNR 41 dB

Data Transmission

- Data Rate up to 55Mbps
- Video Frame Rate up to:
 - 15 fps @ 2048x1536
 - 22 fps @ 1920x1200
 - 30 fps @ 1280x1024
- Motion JPEG with 20 Levels of Quality
- TFTP and HTTP Image Transmission Protocols
- 100Base-T Ethernet Network Interface

Programmability

- Auto Exposure (AE) and Gain Control (AGC) >120dB
- On-Camera Motion Detection with 64 Detection zones
- Auto Backlight Compensation
- Auto Multi-Matrix White Balance
- 50/60Hz selectable Flicker Control
- Electronic Pan, Tilt, Zoom (PTZ)
- Electronic Image Rotation - Up-Side Down Image Turn
- Resolution Windowing Down to 32x32 Pixels Window
- Programmable Motion Blurring Control for Low-Light Mode
- MoonLight™ Mode - Extended Exposure and Proprietary Noise Cancellation
- Programmable Resolution, Brightness, Saturation, Gamma, Sharpness, Tint
- Picture-in-Picture: Simultaneous Delivery of Full Field of View and Zoomed Images
- Bandwidth & Storage Savings by Running at 1/4 resolution

Electrical

- Opto-Coupled Alarm Input, Opto-Coupled Alarm and Flash Sync Output
- Power Over Ethernet (PoE) or DC Input
- PoE 802.3af/Auxiliary 12V-48V DC
- Power Consumption 3 Watts Maximum
- Optional DC AI Connection

Regulatory Approvals

- FCC and CE compliant

Mechanical

- 3"Wx2.5"Hx2.25"D (w/o lens)
- 8.6 oz or 243 grams (w/o lens)
- C/CS Lens Mount

Environmental

- Operating Temperature 0°C to +50°C
- Storage Temperature -20°C to +60°C
- Humidity 0% to 90% (non condensing)

