

1/3"

1/2"



Model No.	T2314FICS-3	T2616FICS-3	T0412CS-3	T0412FICS-3
Format (")	1/3	1/3	1/3	1/3
Mount	CS	CS	CS	CS
Focal Length (fmm)	2.3	2.6	4	4
Aperture(F)	1.4-16C	1.6-11C	1.2	1.2-16C
Angle of View(HOR)°	113.3	99.6	63.9	63.9
M.O.D. (m)	0.2	0.3	0.2	0.2
Effective Aperture Front (φmm)	22.8	16.4	15.5	15.5
Rear (φmm)	7.0	8.0	8.5	8.5
Front Filter Thread (φMxP=)	-	-	-	-
Dimensions (φxD) or (φxHxD) or (WxHxD) mm	φ34.5×35.4	φ34.5×34.7	φ31×30.5	φ34.5×33
Weight (g)	43	45	25	36
NOTES			No Iris Manual Focus	



Model No.	T0812CS-3	T0812FICS-3	H2616FICS-3	H3616FICS-3
Format (")	1/3	1/3	1/2	1/2
Mount	CS	CS	CS	CS
Focal Length (fmm)	8	8	2.6	3.6
Aperture(F)	1.2	1.2-16C	1.6-11C	1.6-16C
Angle of View(HOR)°	34.7	34.7	127.9	99.2
M.O.D. (m)	0.2	0.2	0.1	0.2
Effective Aperture Front (φmm)	15.0	15.0	23.2	16.5
Rear (φmm)	8.8	8.8	7.5	9.0
Front Filter Thread (φMxP=)	-	-	-	-
Dimensions (φxD) or (φxHxD) or (WxHxD) mm	φ31×27.8	φ34.5×33	φ34.5×34.7	φ34.5×33
Weight (g)	30	37	45	38
NOTES	No Iris Manual Focus			



Model No.	H4514FICS-3	H0614FICS-3	H1214FICS-3
Format (")	1/2	1/2	1/2
Mount	CS	CS	CS
Focal Length (fmm)	4.5	6	12
Aperture(F)	1.4-16C	1.4-16C	1.4-16C
Angle of View(HOR)°	79.6	58.3	30.4
M.O.D. (m)	0.2	0.2	0.3
Effective Aperture Front (φmm)	15.8	10.8	13.0
Rear (φmm)	9.0	8.6	8.8
Front Filter Thread (φMxP=)	-	-	-
Dimensions (φxD) or (φxHxD) or (WxHxD) mm	φ34.5×33	φ34.5×33	φ34.5×33
Weight (g)	36	35	33
NOTES			

1/2"

2/3"



Model No.	H3616FI	H0612FI	H1212FI
Format (")	1/2	1/2	1/2
Mount	C	C	C
Focal Length (fmm)	3.6	6	12
Aperture(F)	1.6-16C	1.2-16C	1.2-16C
Angle of View(HOR)°	92.6	57.1	29.5
M.O.D. (m)	0.2	0.2	0.3
Effective Aperture Front (φmm)	20.3	22.5	16.5
Rear (φmm)	9.9	12.4	10.5
Front Filter Thread (φMxP=)	-	-	-
Dimensions (φxD) or (φxHxD) or (WxHxD) mm	φ39×28.9	φ39×33.5	φ39×31.6
Weight (g)	50	55	45
NOTES			



Model No.	M8513	M1614	M1614WI
Format (")	2/3	2/3	2/3
Mount	C	C	C
Focal Length (fmm)	8.5	16	16
Aperture(F)	1.3-16C	1.4	1.4-16C
Angle of View(HOR)°	57.4	30.9	30.9
M.O.D. (m)	0.2	0.25	0.25
Effective Aperture Front (φmm)	20.0	14.5	14.5
Rear (φmm)	12.0	10.8	10.8
Front Filter Thread (φMxP=)	-	-	-
Dimensions (φxD) or (φxHxD) or (WxHxD) mm	φ39×31.6	φ31×28	φ39×28.9
Weight (g)	50	25	41
NOTES		No Iris Manual Focus	

Note: CS-mount lenses can be used with CS-mount cameras only. By using 5mm Adapter Ring, C-mount lens can be applied to CS-mount cameras.

MANUAL IRIS / CS-MOUNT

MANUAL IRIS / C-MOUNT